

XTCII SERIES WATERMAKER SYSTEMS

The Dometic SeaXchange XTCII lets you enjoy the freedom of fully automatic operation with the backup reliability of mechanical override for full redundancy and peace of mind.

**FULLY AUTOMATIC
WITH MECHANICAL
REDUNDANCY**

**INTEGRATED
COLOR TOUCH SCREEN**

**NEMA 2000
CONNECTIVITY**



230V/60Hz
220V/50Hz



SEAWATER

THE ONLY AUTOMATIC WATERMAKER WITH MECHANICAL REDUNDANCY



With one-touch operation and programmable logic, the XTCII keeps your water tanks full. A mechanical override stands by in case of computerized automation failure. The XTCII is built for marine reliability, durability, and rust resistance. Enjoy convenience, reliability, and peace of mind. The XTCII automatic watermaker with mechanical redundancy provides up to 2,200 GPD/8,328 LPD using reverse osmosis technology to turn seawater into freshwater. Programmable logic control software monitors and regulates all system functions without operator intervention.

KEY BENEFITS

- NEMA 2000 connectivity
- 2-in-1 modular or compact frame design
- Durable and reliable
- Automatic freshwater flush
- High-rejection seawater membranes
- Fully upgradable from 600 to 2,200 GPD/2,271 to 8,328 LPD
- The only fully automatic watermaker with mechanical redundancy
- Integrated 7 in./178 mm color touchscreen
- 316SS high-pressure pump
- TEFC motor with thermal motor protection



1. EASY TO USE

Color touchscreen with graphical display for easy operation



2. BUILT-IN REDUNDANCY

Mechanical override in case of computerized automation failure



3. QUIETER

Vibration-isolation mounts reduce noise and vibration

Model	XTCII600	XTCII1200	XTCII1800	XTCII2200
Capacity Per Hour (gal/m ³)	600/2.27	1200/4.54	1800/6.81	2200/8.32
Capacity Per Hour (gal/l)	25/95	50/190	75/284	90/340
Booster Pump 230/220v//60/50hz (amp)	4.10/3.10	4.10/3.10	4.10/3.10	4.10/3.10
High Pressure Pump 230/220v//60/50hz (amp)	9.9/9	9.9/9	9.9/9	9.9/9
Total Amps (230/220//60/50)	14/12.1	14/12.1	14/12.1	14/12.1
Breaker Size (amp)	30	30	30	30
Membrane Quantity	1	2	3	4
Net Weight (lbs/kg)	136/62	156/71	176/80	196/89
Shipping Weight (lbs/kg)	230/105	250/114	270/123	290/132
Shipping Dimensions (H x W x D)(in/cm)	30 x 42 x 48 / 76 x 107 x 122			

*Production may vary +/- 20%